

GP ENVIROCOAT 300

Epoxy Polyester Powder



Product Description

GP Envirocoat 300 is a thermosetting powder based on epoxy & hybrid polyester resin that provides excellent mechanical properties, over bake resistance & outstanding flow-leveling characteristics.

Corrosion protection	★★★★
Chemical resistance	★★★
Mechanical properties	★★★★
UV resistance	★★

Product Range

GP Envirocoat 300 powders are available in glossy, semi-glossy, matt, texture & structure finish, in a range of standard shades or a customized shade to suit the end user's requirement. For exact shade requirements, please contact your local GP office.

Substrates & Surface Preparation

Type of Substrates	Surface Preparation
Steel	Iron phosphating/Low weight zinc phosphate
Aluminium	Chromatization

Powder Characteristics

Powder Properties	Characteristics
Powder Type	Epoxy Polyester
Partical Size	Suitable for Electrostatic Spray
Specific Gravity	1.4 to 1.8 g/cm ³ depending upon color
Storage Condition	Dry & cool conditions below 30°C
Shelf Life	12 months
Stoving Schedule	10 to 15 minutes at 180°C

Performance Properties

Property	Test Standard	Results
Adhesion	ASTM D3359	GT-0 to pass
Erichsen Cupping	ISO 1520	6 - 8 mm to pass
Impact Test	ASTM D2794	60 - 150 kg/cm (Direct/Indirect) to pass
Flexibility Test	ASTM D522	6.25 mm to pass

Application Conditions

Test Method	Application Parameters
Electrostatic Powder Spray	60 - 100 KV
DFT Application	50 - 70 microns

Chemical & Durability Tests

Property	Test Standard	Test Duration	Results
Resistance to Neutral Salt Spray	ASTM B117	500 Hours	No blistering, 3 mm creepage from scribe
Resistance to Humid Atmospheres	ISO 6270-2	500 Hours	No blisters or other failures
Chemical Resistance	-	-	Generally excellent resistance to most acids, alkalis & oils at normal temperatures

Note:

- Above table is for indication purpose only
- Data is based on assumption of pretreatment of seven tank phosphating
- Creepage considered is from either side of the scribe as per ASTM B117

Typical Application

Indoor Furniture, Appliances, White Goods, Switch Gears, Computer Peripherals, Indoor Lighting Fixtures etc.

Pack Size

10 KG
20 KG

Safety Precaution

Please consult the Material Safety Data Sheet (MSDS).

Disclaimer:

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purpose. In no event shall Grand Polycoats assume liability for damages or losses of any kind of nature that result from the use of or reliance upon this information and recommendations. Grand Polycoats expressly disclaims any representations and warranties of any kind, whether express or implied, as to the accuracy, completeness, non-infringement, merchantability and/or fitness for a particular purpose (even if Grand Polycoats is aware of such purpose) with respect to any information and recommendations provided. References to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Grand Polycoats reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Grand Polycoats Co. Pvt. Ltd.

204, Siddharth Complex,
R.C. Dutt Road, Vadodara - 390007,
Gujarat, India

+91 265 6164200/01

marketing@grandpolycoats.com www.grandpolycoats.com

